
XDL-3500×400 continuous frying machine



Specification

1	Frying product	chicken, hamburger patty, snack foods,etc...
2	Heating method	electricity
3	Rated power	90kw
4	Frying temperature	depends
5	Frying temperature range	80-300°C
6	Temperature precision	±1°C
7	Frying time	depends
8	Frying time control range	10s-360s,frequency adjustable
9	Overall dimension	3500*1500*1900mm(L*W*H) 600 кг
10	Oil volume	400L
11	Mesh belt width	400mm
12	Mesh belt type	Depends

2. detail information

No.	Item	introduction	Photos
1	continuous fryer	<p>Automatic continuously working;</p> <ul style="list-style-type: none"> ●Pot body made of 4mm 304 stainless steel, baseboard is 5mm thickness. ●Pot body shell made of 1.5mm 304 stainless steel. ● Water leakage test to make sure the leakproofness after welding. ● Aluminum silicate insulation materials is filled between pot body and shell. ●Drain valve is installed on the bottom of fryer ●Oil vent installed on the in-feed of the fryer to prevent floating and remaining at the entry. 	
1.1	Hoisting system	<ul style="list-style-type: none"> ●Use chains hoisting system. ●Can hoist the fume exhaust cover individually. ●Can hoist the cover, belt holder and heating tubes together ● Convenient to clean the mesh belt and fume exhaust cover. ●Use the safety bumper to make sure the belt holder can not fall down when it lifted. ●Automatically cut off heating tubes' power when hoisting the cover. 	
1.2	Automatic control box	<p>oil temperature is tested by sensor and transfer to controller. It will stop heating after reaching the set temperature and alarm if beyond set temperature</p> <ul style="list-style-type: none"> ●Two temperature measurement point, control temperature of each parts of fryer respectively. ●Heating tubes made of stainless steel. ●Each group of heating tubes can power off 	

1.3	Mesh belt conveying system	<ul style="list-style-type: none"> ●Belt speed is frequency controlled. ●The mesh belt holder made of 3mm stainless steel. <ul style="list-style-type: none"> ●The exhaust cover and belt holder can be lifted individually, easy cleaning. ●The bearing and seat is made of stainless steel 304. ●The gap of double belt is 30-60 mm(adjustable) ●Transmission use gear reducer with low noise. 	
1.4	Lampblack exhausting system	<ul style="list-style-type: none"> ●Exhaust cover is made of 1.5mm stainless steel 304. ●The cover and exhaust pipes have vapour extraction system. ●Two fume Exhaust pipes ,each is 6m long,made of 304 stainless steel. ●Axial flow fan installed on the end of each exhaust ● Control valve installed on the bottom of exhaust seat. 	
1.5	Non-stick PTFE mesh belt	<p>Non-stick to the mesh belt with the help of the PTFE.</p> <p>It is 1m long at the entrance of the frying machine</p>	

3. price list

order	Name	Model	QTY	Unit price(usd\$)	Total price (usd\$)
1	Continuous frying machine	XDL-3500*400	1		
1.1	Hoisting system		1		
1.2	Automatic control box		1		
1.3	Mesh belt conveying system		2		
1.4	Lampblack exhausting system		1		

1.5	Non-sitck PFTE material		1		
	FOB QINGDAO PRICE	A COMPLETE LINE			

Terms:

1. *comodity name:XDL-3500*400 continuous frying machine.*
2. *Price: **USD** _____,FOB Qingdao*
3. *Payment term: 30% advance payment by T/T, the balance paid by T/T before shipment.*
4. *Delivery time: 30days after receiving 30% of the whole payment.*
5. *Valid time: This quotation is valid for one month.*
6. *Packing: Plywood case or customized.*
7. *Installation: Overseas technical support is available.*
8. *Quality Guarantee: One year for free, fixing for all life time.*

